



### Communication continues to evolve each day, and to keep up, so must your desktop telephone.

Apivio brings you the obvious next step in desktop phone development. The new UT880s desktop telephone re-invents the office phone by integrating the traditional desktop telephone and tablet into one innovative, feature-packed device. The UT880s - revolutionizes your desktop experience.

### Technology is evolving at a faster pace than ever before.

To keep up, desktop telephones need to evolve to meet the ever changing communication demands of today's workforce. The UT880s provides you with easy access to your Unified Communications (UC) desktop/mobile client. Get UC functionality - corporate directories, presence, instant messaging, unified messaging, and call control - available at your fingertips.

With the UT880s, your workforce will be able to take it to the next level with a flexible and extensible device that conforms to multiple working styles and helps improve efficiency and productivity.

#### Features

- USB port
- Full seven inch color display with multi-touch capabilities
- Multi-line SIP client that emulates any telephone
- Open interface for application development
- BroadSoft platform voice functionality and hands-free, wide-band speakerphone
- Integrated Bluetooth capability
- Built-in camera for video call and picture/video applications



# Make Upgrading **Obsolete**



## Simple software updates keeps your phone current.

Many businesses are afraid that if they upgrade with phones today, something better will come out tomorrow.

With the UT880s, simple software updates are all that is required to keep your desktop phone current. No need to purchase a new phone, protecting your investment.

The UT880s' interface is designed to improve the overall user experience while remaining intuitive - with no extensive training needed. Global icons indicate status at-a-glance including notification of new voice or instant messages, missed calls, the telephone's user's current presence status, and the device's current date protection mode.

## Specifications

	Features	UT880S Desktop Telephone	
<b>HARDWARE</b>	LCD Display	7 inch TFT LCD WVGA (1024 x 600) with Backlight. 16.7M Colors	
	Touch Screen	Capacitive 4 Finger Multi-touch Window	
	Camera	Front Facing Built-in Camera	
	Incoming Call Lamp	3 Colors: Red, Green, Blue	
	Bluetooth	Bluetooth V2.1 +EDR	
	Audio		HD Audio: Both on handset and speaker
			Hands-free Microphone: Omni-Directional
			Wideband Speaker: Wideband G722HD; Narrow Band: G711 $\mu$ law/A-law, G729A
			Full Duplex Support
	Network		Handset/Headset RJ 9 Independent Connection
			Protocol support: IPv4
			Ethernet Port: Type- Dual Switched auto-sensing Built-in 2 Port Switch LAN Port: 10/100/1000 Mbps with integrated PoE PC Port: 10/100/1000 Mbps
	Power over Ethernet (PoE)		IEEE 802.3af Compliant Class 0. No AC Jack
SD Card I/F		Micro SD Card Connector supports version	
USB Port		Host Port - Version: USB 2.0; Connector: Type A	
Flash Memory		4GB MLC NAND Flash	
SDRAM Memory		1GB (Shared with internal applications and dialer)	
<b>SOFTWARE</b>	VOIP	RFC 3261 - SIP Version 2 <ul style="list-style-type: none"> <li>• Ready to support IPv6</li> <li>• Multiple SIP Users (accounts)</li> <li>• Support Secure SIP (SIPS)</li> </ul> RFC 3550 - A Transport Protocol for Real-Time Applications (RTP) RFC3711 - The Secure Real-Time Transport Protocol RFC4566 - SDP: Session Description Protocol. backward compatible with RFC2327	
	CODEC	Voice Call: <ul style="list-style-type: none"> <li>• Narrowband: G711<math>\mu</math>-law/A-law</li> <li>• Wideband: G722 Wide-band</li> </ul> Video Call: <ul style="list-style-type: none"> <li>• H.264</li> </ul>	
	Call Operation	Voice Call, Video Call, Call Forwarding, Call Transfer, Call Screen/Do Not Disturb, Call Pick-up, Call Waiting, Call Mute, Call Hold, Add Call, Call Log, Contacts, Speaker Phone, Headset Mode, Bluetooth Mode	
	Sample Applications	Browser, calculator, calendar, camera, email, gallery, movie studio, music	
<b>EXTERIOR</b>	Dimensions (W x D x H:mm:W" x D" x H")	192 x 255 x 150mm; 7.56" x 10.4" x 5.91"	
	Weight (Approx. kg and lbs.)	1kg; 2.2 lbs.	
<b>OPERATING CONDITIONS</b>	Operating Time	5°-50°	
	Humidity	10-95%	
<b>PLATFORMS</b>	Support On	Various IP PBX and Soft-Switches	